



ŞAHİN DALGIÇ
MOTOR POMPA

SANTRİFÜJ POMPALAR

SANTRİFÜJ POMPALAR - CENTRIFUGAL PUMPS

Pompa Model Pump Model	Güç Power		Pompa Pump Bore		Basılan Su (Debi)					
					Q (m³ / saat)					
	Hp	Kw	Giriş Suction	Çıkış Delivery	0	4,4	11,2	15,5	17,5	19
					Basma Yüksekliği (Hm) mss					
ŞDP 53 WSY	1,5	1,1	2"	2"	29	27	23	19	13	3
					0	9,2	15	17,6	18,5	19,5
ŞDP 56 WSY	2	1,5	2"	2"	33	28	23	18	13	3
					0	14	21	47	55	60
ŞDP 57 WSY	2	1,5	3"	2 1/2"	15	14	13	7	5	3
					0	4,1	6,8	10	12	15
ŞDP 58 WSY	3	2,2	2"	2"	34	32	30	25	20	17
					0	10	12	21	28	35
ŞDP 59 WSY	3	2,2	3"	2 1/2"	28	26	25	20	15	10
					0	1,5	9,8	11	12	20
ŞDP 60 WSY	4	3	2"	2"	43	41	38	33	28	13
					0	19	23	33	37	44
ŞDP 61 WSY	4	3	3"	2 1/2"	30	29	28	23	18	3
					0	19	23	33	37	44
ŞDP 62 WSY	5,5	4	3"	3"	30	29	28	23	18	3
					0	5	28	41	50	57
ŞDP 63 WSY	5,5	4	3"	2 1/2"	32	31	28	23	18	3
					0	5	10	32	40	59
ŞDP 64 WSY	7,5	5,5	3"	3"	35	34	33	28	23	8
					0	35	51	68	79	85
ŞDP 65 WSY	10	7,5	3"	3"	38	36	33	28	23	3
					0	3,5	10,7	13	16	18
ŞDP 70 WSY	3	2,2	2"	2"	45	42	35	30	25	20



- Maksimum ortam sıcaklığı +40 °C
- Maksimum su sıcaklığı +60 °C
- Maksimum emiş 6-7 metre
- Alüminyum fanlıdır
- Isınmaya karşı dayanıklıdır

- Maximum ambient temperature +40 °C
- Maximum liquid temperature up to +60 °C
- Maximum suction lift up to 6-7 meter
- Aluminium impeller
- It is resistant to heat